









Державки для наружного точения

Типы оснастки	Кат. №	Наличие		Размеры (мм)								Станд. радиус при вершине r_E	Применяемые пластины	Форма
		R	L	h	b	L ₁	L ₂	h ₁	f	f ₂				
<div>Наружное профилирование</div> <div>MDJNR/L</div> <div></div> <div>Исполнение режущей кромки J</div>	MDJNR/L1616H11			16	16	100	30	16	20	—	0.8	DN□□1104□□ 55°/6° ➤ 2-52 ~	<div></div> <div>Показано правое исполнение R</div>	
	MDJNR/L2020K15			20	20	125		20	25			0.8		DN□□1504□□ 55°/6° 55°/6°
	MDJNR/L2525M15	●		25		150		25						DN□□1506□□ 55°/6° ➤ 2-52 ~
	MDJNR/L3225P15				25		38		32	19				T-CBN ➤ 3-7 ~ T-DIA ➤ 3-21 ~
	MDJNR/L3232P15			32		170		32		40		0.8		DN□□1507□□ 55°/6° ➤ 2-60 ~
	MDJNR/L2020K15C			20	20	125		20	25					DN□□1506□□ 55°/6° ➤ 2-52 ~
	MDJNR/L2525M15C			25		150		25						
	MDJNR/L3225P15C						38		32	19				
	MDJNR/L3232P15C			32		170		32		40				
<div>Профилирование</div> <div>MDQNR/L</div> <div></div> <div>Исполнение режущей кромки Q</div>	MDQNR/L1616H11			16	16	100	30	16	20	—	0.8	DN□□1104□□ 55°/6° ➤ 2-52 ~	<div></div> <div>Показано правое исполнение R</div>	
	MDQNR/L2020K15			20	20	125		20	25			0.8		DN□□1504□□ 55°/6° 55°/6°
	MDQNR/L2525M15			25		150		25						DN□□1506□□ 55°/6° ➤ 2-52 ~
	MDQNR/L3225P15						36		32	—				T-CBN ➤ 3-7 ~ T-DIA ➤ 3-21 ~
	MDQNR/L3232P15			32		170		32		40				
<div>Наружное профилирование</div> <div>MDPNN</div> <div></div> <div>Исполнение режущей кромки P</div>	MDPNN1616H11			16	16	100	36	16	8		0.8	DN□□1104□□ 55°/6° ➤ 2-52 ~	<div></div>	
	MDPNN2020K15			20	20	125		20	10			0.8		DN□□1504□□ 55°/6° 55°/6°
	MDPNN2525M15	●		25		150		25						DN□□1506□□ 55°/6° ➤ 2-52 ~
	MDPNN3225P15						42		12.5					T-CBN ➤ 3-7 ~ T-DIA ➤ 3-21 ~
	MDPNN3232P15			32		170		32		16				
<div>Наружное профилирование</div> <div>MTJNR/L</div> <div></div> <div>Исполнение режущей кромки J</div>	MTJNR/L2020K16			20	20	125		20	25			0.8	TN□□1603□□ TN□□1604□□ 60°/60° ➤ 2-70 ~	<div></div> <div>Показано правое исполнение R</div>
	MTJNR/L2525M16	●		25		150		25					T-CBN ➤ 3-8 ~ T-DIA ➤ 3-21 ~	
	MTJNR/L3225P16				25		28		32					
	MTJNR/L2525M22			25		150		25				0.8	TN□□2204□□ 60°/60° ➤ 2-70 ~	
	MTJNR/L3225P22						32		32					
	MTJNR/L3232P22			32		170		32		40				

● : Складские позиции