





T-тип

Державки для наружного точения

Положительный передний угол
Система конического крепления

Тип оснстки	Кат. №	Наличие		Размеры (мм)								Станд. угол при вершине	Применяемые пластины	Форма	
		R	L	h	b	L ₁	L ₂	h ₁	f	f ₂					
Точение TRACN  Исполнение режущей кромки A	TRACN2020K05	●		20	20	125		20	20.31			5	-	RT05 ○ ▶ 2-142	
	TRACN2525M05	●		25	25	150		25	25.31						
	TRACN2020K06	●		20	20	125		20	20.37			6	-	RT06 ○ ▶ 2-142	
	TRACN2525M06	●		25	25	150		25	25.37						
	TRACN2525M08	●		25	25	150	25	25	25.52			8	-	RT08 ○ ▶ 2-142	
Точение-Снятие фаски TRDCN  Исполнение режущей кромки D	TRDCN2020K05	●		20	20	125		20	12.5			5	-	RT05 ○ ▶ 2-142	
	TRDCN2525M05	●		25	25	150		25	15						
	TRDCN2020K06			20	20	125		20	13			6	-	RT06 ○ ▶ 2-142	
	TRDCN2525M06	●			25	25	150		25	15.5					
	TRDCN2525M08			25	25	150	25	25	16.5			8	-	RT08 ○ ▶ 2-142	

● : Складские позиции

4

Державки ТАС