



**L/D = 3**

Диам. сверла øDc	Кат. №	Наличие	Размеры (мм)					Макс. смещ.	Применяемые пластины	Зажимной винт	Ключ					
			øDs	øD	l	ls	L									
12.5	TDX125W20-3	●	20	25	37.5	43	100	XPMT040104R-D*	CSTB-2	T-6D						
13.0	TDX130W20-3	●			39		102				0.7					
13.5	TDX135W20-3	●			40.5		104				0.5					
14.0	TDX140W20-3	●			42		106				0.4					
14.5	TDX145W20-3	●			43.5		108				0.3					
15.0	TDX150W20-3	●		45	110		0.9									
15.5	TDX155W20-3	●		25	32		46.5				50	112	XPMT050204R-D*	CSTB-2L040	T-6D	
16.0	TDX160W20-3	●					48					114				0.6
16.5	TDX165W20-3	●					49.5					116				0.5
17.0	TDX170W20-3	●					51					118				0.4
17.5	TDX175W25-3	●	52.5			127	1.2									
18.0	TDX180W25-3	●	54			129	1.1									
18.5	TDX185W25-3	●	55.5			131	0.9									
19.0	TDX190W25-3	●	57	133	0.8											
19.5	TDX195W25-3	●	25	37	58.5	50	135	XPMT06X308R-D*	CSTB-2.2R	T-7D						
20.0	TDX200W25-3	●			60		137				0.5					
20.5	TDX205W25-3	●			61.5		139				0.4					
21.0	TDX210W25-3	●			63		141				0.3					
21.5	TDX215W25-3	●			64.5		143				0.2					
22.0	TDX220W25-3	●			66		145				1.2					
22.5	TDX225W25-3	●			67.5		147				1.1					
23.0	TDX230W25-3	●			69		149				0.9					
23.5	TDX235W25-3	●			70.5		151				0.8					
24.0	TDX240W25-3	●			72		153				0.7					
24.5	TDX245W25-3	●	32	40	73.5	55	155	XPMT07H308R-D*	CSTB-2.5	T-8D						
25.0	TDX250W25-3	●			75		157				0.4					
25.5	TDX255W25-3	●			76.5		159				0.3					
26.0	TDX260W25-3	●			78		161				0.2					
27.0	TDX270W32-3	●			81		170				1.5					
28.0	TDX280W32-3	●			84		174				1.2					
29.0	TDX290W32-3	●			87		178				1.0					
30.0	TDX300W32-3	●			90		182				0.7					
31.0	TDX310W32-3	●			93		186				0.4					
32.0	TDX320W32-3	●			96		190				0.2					
33.0	TDX330W40-3	●	40	50	99	65	204	XPMT110412R-D*	CSTB-4	T-15D						
34.0	TDX340W40-3	●			102		208				2.1					
35.0	TDX350W40-3	●			105		212				1.8					
36.0	TDX360W40-3	●			108		216				1.5					
37.0	TDX370W40-3	●			111		220				1.3					
38.0	TDX380W40-3	●			114		224				1.0					
39.0	TDX390W40-3	●			117		228				0.7					
40.0	TDX400W40-3	●			120		232				0.5					
41.0	TDX410W40-3	●			123		236				0.2					
42.0	TDX420W40-3	●			55		55				126	65	240	XPMT150512R-D*	CSTB-5	T-20D
43.0	TDX430W40-3	●	129	244		2.9										
44.0	TDX440W40-3	●	132	248		2.6										
45.0	TDX450W40-3	●	135	252		2.3										
46.0	TDX460W40-3	●	138	256		2.1										
47.0	TDX470W40-3	●	141	260		1.8										
48.0	TDX480W40-3	●	144	264		1.5										
49.0	TDX490W40-3	●	147	268		1.3										
50.0	TDX500W40-3	●	150	272		1.0										
51.0	TDX510W40-3	●	153	276		0.7										
52.0	TDX520W40-3	●	156	280	0.5											
53.0	TDX530W40-3	●	159	284	-											
54.0	TDX540W40-3	●	162	288	-											

Примечание: L/D = Глубина отверстия/Диаметр сверла

● : Складские позиции

Связанные страницы

Стандартные условия резания (11-14)

Технический справочник (15-1)