



L/D = 5

Диам. сверла øDs	Кат. №	Наличие	Размеры (мм)					Макс. смещ.	Применяемые пластины	Зажимной винт	Ключ			
			øDs	øD	l	ls	L							
12.5	TDX125W20-5	●	20	25	62.5	43	128	XPMT040104R-D*	CSTB-2	T-6D				
13.0	TDX130W20-5	●			65.0		131				0.7			
13.5	TDX135W20-5	●			67.5		134				0.5			
14.0	TDX140W20-5	●			70.0		137				0.4			
14.5	TDX145W20-5	●			72.5		140				0.3			
15.0	TDX150W20-5	●		75.0	143		0.9							
15.5	TDX155W20-5	●		32	77.5		146				0.8	XPMT050204R-D*	CSTB-2L040	T-6D
16.0	TDX160W20-5	●			80.0		148				0.6			
16.5	TDX165W20-5	●			82.5		152				0.5			
17.0	TDX170W20-5	●			85.0		154				0.4			
17.5	TDX175W25-5	●	87.5		165	1.2								
18.0	TDX180W25-5	●	25	32	90.0	50	168	XPMT06X308R-D*	CSTB-2.2R	T-7D				
18.5	TDX185W25-5	●			92.5		171				0.9			
19.0	TDX190W25-5	●			95.0		173				0.8			
19.5	TDX195W25-5	●			97.5		176				0.7			
20.0	TDX200W25-5	●			100.0		180				0.5			
20.5	TDX205W25-5	●		102.5	182		0.4							
21.0	TDX210W25-5	●		105.0	185		0.3							
21.5	TDX215W25-5	●		107.5	188		0.2							
22.0	TDX220W25-5	●		110.0	191		1.2							
22.5	TDX225W25-5	●		37	112.5		193				1.1	XPMT07H308R-D*	CSTB-2.5	T-8D
23.0	TDX230W25-5	●	115.0		196	0.9								
23.5	TDX235W25-5	●	117.5		199	0.8								
24.0	TDX240W25-5	●	120.0		202	0.7								
24.5	TDX245W25-5	●	122.5		205	0.5								
25.0	TDX250W25-5	●	125.0		208	0.4								
25.5	TDX255W25-5	●	127.5		211	0.3								
26.0	TDX260W25-5	●	130		213	0.2								
27.0	TDX270W32-5	●	32		40	135	55	225	XPMT08T308R-D*	CSTB-3	T-9D			
28.0	TDX280W32-5	●				140		231						
29.0	TDX290W32-5	●		145		237		1.0						
30.0	TDX300W32-5	●		150		243		0.7						
31.0	TDX310W32-5	●		155		248		0.4						
32.0	TDX320W32-5	●		160		254		0.2						
33.0	TDX330W40-5	●		40		50		165				65	271	XPMT110412R-D*
34.0	TDX340W40-5	●	170		277		2.1							
35.0	TDX350W40-5	●	175		283		1.8							
36.0	TDX360W40-5	●	180		288		1.5							
37.0	TDX370W40-5	●	185		295		1.3							
38.0	TDX380W40-5	●	190		300	1.0								
39.0	TDX390W40-5	●	195		306	0.7								
40.0	TDX400W40-5	●	200		312	0.5								
41.0	TDX410W40-5	●	205		318	0.2								
42.0	TDX420W40-5	●	55		210	324	3.1	XPMT150512R-D*	CSTB-5	T-20D				
43.0	TDX430W40-5	●		215	330	2.9								
44.0	TDX440W40-5	●		220	336	2.6								
45.0	TDX450W40-5	●		225	341	2.3								
46.0	TDX460W40-5	●		230	348	2.1								
47.0	TDX470W40-5	●		235	353	1.8								
48.0	TDX480W40-5	●		240	359	1.5								
49.0	TDX490W40-5	●		245	365	1.3								
50.0	TDX500W40-5	●		250	370	1.0								
51.0	TDX510W40-5	●		255	376	0.7								
52.0	TDX520W40-5	●	260	382	0.5									
53.0	TDX530W40-5	●	265	388	-									
54.0	TDX540W40-5	●	270	393	-									

Примечание: L/D = Глубина отверстия/Диаметр сверла

● : Складские позиции

Связанные страницы

Стандартные условия резания (11-14)

Технический справочник (15-1)